Wiring Accessories – Cutting & Stripping Tools

Wire Cutting and Stripping Tools

Wire Cutting and Stripping Tools			
Part Number	Description	Qty	Price
<u>DN-WS</u>	Cutting and stripping tool with replaceable blades and jaw inserts; includes (1) DN-WSJ blade Approximate dimensions: 7.5 x 4.8 x 0.8 in (191 x 123 x 20 mm); Weight: 4.8 oz (136g)	1	
DN-WSJ	DN-WS replacement straight-blade insert; for PVC insulations; 34-8 AWG (0.02-10 mm²)	1	
DN-WSMMC	DN-WS 16 mm2 blade insert; 12-5 AWG (4-16 mm²)	1	
DN-WSVBC	DN-WS V-blade insert; for harder insulations such as PTFE & PVC; 28-12 AWG (0.1-4 mm²)	1	
DN-WSRJ	DN-WS replacement jaw inserts	2	
DN-CST	Cable stripping tool; cable diameters 0.1-0.43 in (2.5-11 mm) with insulation up to 0.04 in (1.0 mm) thick Approximate dimensions: 3.6 x 1.6 x 0.8 in (90.5 x 39.5 x 19 mm); Weight: 0.9 oz (28g)	1	
DN-CST-BLADE	DN-CST replacement blade	1	

Self-Adjusting Cut and Strip Tool DN-WS

- · Widest stripping capacity of any tool of its type
- Easily interchangeable stripping cassettes are available for stripping a wide range of most modern insulation types, from PVC to PTFE; color coded by stripping blade type
- No additional tools required to change stripping blade cassettes
- Precise adjustability allows stripping of various insulation thicknesses without damage to conductors
- Easy snag-free wire removal after stripping
- · Ergonomic design with soft-grip handle
- Light weight and strong; molded in highstrength plastic with twice the strength of standard nylon; tested 150k cycles
- Cutting capacity: Stranded conductors to 8AWG (10 mm²) Solid conductors to 16 AWG (1.5 mm²)

Cable Stripping Tool DN-CST

Small, simple, safe, and precise tool for removing insulation from copper and fiber optic audiovisual, data transmission, instrumentation, signal, and telephone cables.

- Precise: 9-position blade height adjustment wheel for fine adjustability and repeatability
- Easy to use: Squeeze the tool together to open the stripping cavity, insert cable, rotate once, and remove tool from cable. Separately pull scrap insulation off of cable.
- Safe: Smooth, rounded, pocketable, and lightweight design; no exposed blades
- Tough: Impact resistant nylon tested to over 50k cycles
- Economical: Replacement blades available
- Cable capacity: Ø 0.1-0.43 in (2.5-11 mm)
- Insulation thickness: Up to 0.04 in (1.0 mm)





DN-CSTPrecision Stripping Tool
[Squeeze, insert cable, rotate, & remove]

DN-CST-BLADE Replacement Blade



Precision Stripping Tool Easily replaceable blade