

CPU Module

D2-BAT-1

Battery (Replacement)

A battery is included with the P2-550 CPU module, but is not installed. The battery can be installed to retain the Time and Date along with any Tagname values that are set up as retentive.

The battery is not needed for program backup.

Battery (Optional)

D2-BAT-1 Coin type, 3.0 V Lithium battery, 560mA, battery number CR2354

Note: Although not needed for program backup, a battery is included with the P2-550. Install this battery if you want the CPU to retain the Time and Date along with any Tagname values that you have set up as retentive.

Step One:

Press spring lock and swing battery compartment away from CPU.



Step Two:

Insert battery and close compartment.




Take care to insert battery behind metal tab.

MICSD-16G

Micro SD Card

Used for data logging or project transfers.



Micro SD Specifications

Port Name	MICRO SD			
Description	Standard Micro SD socket for data logging or program transfer			
Maximum Card Capacity	32GB			
Transfer Rate (ADATA microSDHC Class 4 memory card)	Mbps	Minimum	Typical	Maximum
	Read	14.3	14.4	14.6
	Write	4.8	4.9	5.1
Port Status LED	Green LED is illuminated when card is inserted/detected			



Note: Card not included with unit.

Pin	SD
1	DAT2
2	CD/DAT3
3	CMD
4	VDD
5	CLK
6	VSS
7	DAT0
8	DAT1