



**TAP-3000**



**TAP-1000**



For a variety of cable options see our website [website](#)

The NITRA Total Air Prep (TAP) unit is the latest technology for compressed air preparation. A single, high flow unit contains an automatic drain air filter with clogged filter indicator, relieving regulator, lockable shut-off valve, pressure gauge and air dump. Electric models also have an adjustable electric soft start / shut-off valve and an adjustable pressure switch with indicator LEDs. Interchangeable inlet and outlet port inserts allow the TAP to easily mount to most pipe sizes.

## Features:

- 20 micron air filter with automatic drain (optional 5 micron filter element sold separately)
- 0-120 psi operating range
- Units ship with 1/2" NPT inlet/outlet ports. Optional NPT or BSP port inserts in sizes 1/4" thru 1" (sold separately). Any combination of port sizes all in one small footprint!
- Units ship with panel mounting hardware. Optional thru-panel mount hardware sold separately.


Nitra Total Air Prep (TAP) Units					
Part No.	Price	Description	Weight	Insert Link	Manual Link
<b>TAP-3000</b>		NITRA pneumatic total air prep unit, 1/2in female NPT inlet(s), 1/2in female NPT outlet(s), 0-120 psi (0-8 bar) adjustable range, polycarbonate bowl, automatic drain, clog indicator, manual shutoff valve, soft start valve, pressure switch.	3.0	<a href="#">PDF</a>	<a href="#">PDF</a>
<b>TAP-1000</b>		NITRA pneumatic total air prep unit, 1/2in female NPT inlet(s), 1/2in female NPT outlet(s), 0-120 psi (0-8 bar) adjustable range, polycarbonate bowl, automatic drain, clog indicator, manual shutoff valve.	2.5	<a href="#">PDF</a>	<a href="#">PDF</a>

Nitra Total Air Prep (TAP) Unit Specifications					
Specification	1/4" Units	3/8" Units	1/2" Units	3/4" Units	1" Units
Flow rate at 91psi (6.3 bar) $\Delta p$ 7psi (0.5 bar)	78 scfm, 2200 NI/min	102 scfm, 2900 NI/min	127 scfm, 3600 NI/min		
Flow rate at 91psi (6.3 bar) $\Delta p$ 14psi (1 bar)	85 scfm, 2400 NI/min	116 scfm, 3300 NI/min	141 scfm, 4000 NI/min		
Flow rate on discharge at 14psi (6 bar)	56 scfm, 1600 NI/min				
1/4" Port flow rate of non-regulated filtered air at 91psi (6.3 bar) $\Delta$ pressure 1 bar	64 scfm, 1800 NI/min				
Flow rate of each supplementary 1/4" filtered and regulated air port at 91psi (6.3 bar) $\Delta$ pressure 1 bar*	85 scfm, 2400 NI/min				
Fluid	Compressed air				
Setting Range	0-120 psi (0-8 bar)				
Degree of Filtration	5µm (yellow) or 20µm (white)				
Maximum Inlet Pressure	145psi (10 bar)				
Operating Temperature Range	-10 to 50°C (-14 to 122°F)				
Protection Class	IP 65 with connector				
Mounting	Front, with M5 x 75 screws or back with M6 x 70 screws (screws are included)				
Mounting Position	Vertical				
Direction of Flow	From left to right				
Approvals	CE				

\* Total flow rate from two supplementary outlets and the main one cannot exceed 4000 NI/min at 6.3 bar with  $\Delta P = 1$

Nitra Total Air Prep (TAP) Unit Specifications (TAP 3000 only)					
Specification	1/4" Units	3/8" Units	1/2" Units	3/4" Units	1" Units
<b>Solenoid Valve Voltage</b>	24VDC $\pm$ 10%				
<b>Pressure Interval Settable on the Pressure Switch</b>	7 to 145 psi (0.5 to 10 bar)				
<b>Pressure Switch Hysteresis (not adjustable)</b>	6 to 12 psi (0.4 to 0.8 bar)				
<b>Maximum Pressure Switch Current</b>	0.5 A (protected against overload and short-circuit)				
<b>Maximum Pressure Switch Voltage</b>	3 to 30 VAC/VDC				
<b>Pressure Switch Contacts</b>	Normally Open (NO) and Normally Closed (NC)				
<b>Rated Switching Cycles</b>	$5 \times 10^6$				
<b>Protection Class</b>	IP 65 with connector				
<b>Solenoid Valve Insulation Class</b>	Insulation class = F (155°C or 311°F)				
<b>Switching Time</b>	100% ED				
<b>Electrical Connection</b>	M12 x 1 5-pin to CEI IEC 60947-5-2				

## Wiring



### Cable Assembly Wiring Colors:

**Pin 1 - Brown**

**Pin 2 - White**

**Pin 3 - Blue**

**Pin 4 - Black**

**Pin 5 - Yellow/Green**


*Note: wiring colors are based on AutomationDirect CD12L and CD12M 5-pole cable assemblies.*

**Version with solenoid valve and pressure switch**

## Flow Charts:


1/4"

**Pm = 116 psi - 8 bar**  
**Preset pressure**




3/8"

**Pm = 116 psi - 8 bar**  
**Preset pressure**






1/2" - 3/4" - 1"

**Pm = 116 psi - 8 bar**  
**Preset pressure**






## Dimensions

mm [inches]



**TAP-1000 Series**



**TAP-3000 Series**

See our website for complete Engineering drawings.

Total Air Prep (TAP) - Accessories				
Items	Part No.	Price	Description	Weight (lbs)
	<b>TAP-ACC01</b>		NITRA panel mounting brackets, plated steel. For use with TAP unit. Mounting hardware included.	0.2
	<b>TAP-ACC02</b>		NITRA filter element, replacement, 20 micron, ultra high molecular weight polyethylene (UHMWPE). For use with TAP unit.	0.2
	<b>TAP-ACC03</b>		NITRA regulator, replacement, 0-120 psi (0-8 bar) adjustable range, acetal. For use with TAP unit.	0.3
	<b>TAP-ACC04</b>		NITRA filter element, replacement, 5 micron, ultra high molecular weight polyethylene (UHMWPE). For use with TAP unit.	0.1
	<b>TAP-ACC05</b>		NITRA regulator diaphragm, replacement, brass. For use with TAP unit.	0.1
	<b>TAP-ACC06</b>		NITRA plug and filter element, replacement, 20 micron, acetal. For use with TAP unit.	0.1
	<b>TAP-ACC07</b>		NITRA port insert, 1/4in NPT, anodized aluminum. For use with TAP unit.	0.3
	<b>TAP-ACC08</b>		NITRA port insert, G1/4 BSPP, anodized aluminum. For use with TAP unit.	0.3
	<b>TAP-ACC09</b>		NITRA port insert, 3/8in NPT, anodized aluminum. For use with TAP unit.	0.3
	<b>TAP-ACC10</b>		NITRA port insert, G3/8 BSPP, anodized aluminum. For use with TAP unit.	0.3
	<b>TAP-ACC11</b>		NITRA port insert, replacement, 1/2in NPT, anodized aluminum. For use with TAP unit.	0.3
	<b>TAP-ACC12</b>		NITRA port insert, G1/2 BSPP, anodized aluminum. For use with TAP unit.	0.3

Note: For power cables see our Wiring Devices section online at

Total Air Prep (TAP) - Accessories				
Items	Part No.	Price	Description	Weight (lbs)
	<b>TAP-ACC13</b>		NITRA port insert, 3/4in NPT, anodized aluminum. For use with TAP unit.	0.3
	<b>TAP-ACC14</b>		NITRA port insert, G3/4 BSPP, anodized aluminum. For use with TAP unit.	0.3
	<b>TAP-ACC15</b>		NITRA port insert, 1in NPT, anodized aluminum. For use with TAP unit.	0.3
	<b>TAP-ACC16</b>		NITRA port insert, G1 BSPP, anodized aluminum. For use with TAP unit.	0.3
	<b>TAP-ACC17</b>		NITRA regulator removal wrench, steel. For use with TAP unit.	0.3
	<b>TAP-ACC18</b>		NITRA solenoid valve, replacement. For use with TAP-3000 unit.	0.3
	<b>TAP-ACC20</b>		NITRA automatic drain valve, replacement, acetal. For use with TAP unit.	0.3
	<b>TAP-ACC21</b>		NITRA padlock, replacement, brass. For use with TAP unit.	0.3
	<b>TAP-ACC23</b>		NITRA regulator knob, replacement, 0-120 psi (0-8 bar) adjustable range, acetal. For use with TAP unit.	0.1

**Note:** For power cables see our [Wiring Devices](#) section online at