

SCHMERSAL Non-Illuminated 22mm IP69k Plastic Selector Switches



Black



White


Non-Illuminated 22mm Selector Switches*				
Part Number	Price	Color	Drawing Link	Operation
NWS21GR		Black	PDF	2-position maintained
NWS21WS		White	PDF	
NWT21		Black	PDF	2-position, spring return from right
NWT21WS		White	PDF	
NWS32		Black	PDF	3-position maintained
NWS32WS		White	PDF	
NWT32		Black	PDF	3-position, spring return to center from right or left
NWT32WS		White	PDF	
NWT32		Black	PDF	3-position, spring return to center from right, maintained left
NWT32WS		White	PDF	
NWT321		Black	PDF	3-position, spring return to center from left, maintained right
NWT321WS		White	PDF	

*Operator only. Purchase contact blocks separately.


Selector Switches Specifications	
Toggle material	ABS
Front ring material	ABS, chrome-plated
Front panel thickness	1.5 to 6 mm
Mechanical operations	300,000
Mounting screws tightening torque	0.6 N·m [0.44 lb·ft]
Ambient temperature	0 to +80°C [32 to +176°F]
Shock resistance	< 50g
Vibration resistance	5g
Ingress protection rating	IP67 and IP69K
Standards	IEC 60947-5-1; IEC 60947-1; UL File E57648,CE

Selector switches with 2-positions

NWT21




NWS21



Contact Blocks							
		Mounting Position 1		Mounting Position 3		Mounting Position 2	
Left (0)	Right (1)	N.C. Contact	N.O. Contact	N.C. Contact	N.O. Contact	N.C. Contact	N.O. Contact
X		1	0	1	0	1	0
	X	0	1	0	1	0	1


SCHMERSAL Non-Illuminated 22mm IP69k Plastic Selector Switches

Selector switches with 3-positions



Contact Blocks							
			Mounting Position 1		Mounting Position 3	Mounting Position 2	
Left (1)	Middle (0)	Right (11)	N.C. Contact	N.O. Contact	Free	N.C. Contact	N.O. Contact
X			0	1		1	0
	X		1	0		1	0
		X	1	0	0	1	

Selector switches with 3-positions (mix with latching and spring return)




Contact Blocks							
			Mounting Position 1		Mounting Position 3	Mounting Position 2	
Left (1)	Middle (0)	Right (11)	N.C. Contact	N.O. Contact	Free	N.C. Contact	N.O. Contact
X			0	1		1	0
	X		1	0		1	0
		X	1	0	0	1	

SCHMERSAL Selector Switches

Important: The mounting flange can be mounted in 4 directions. Please have a look on the position of the mounting flange. Only in the two shown directions the truth table is right.

Note: Only on one side are the numbers for the mounting position of the contact blocks.





SCHMERSAL Contact Blocks



EF03.2



EF10.1



EF103.2



EF220.2



EF303.2



EFM

Contact Blocks								
Part Number	Price	Qty.	Drawing Link	Contacts	Mounting Position	Travel Diagram (mm)	Wiring Diagram	Application
EF10.1*		1	PDF	1 N.C.	1			Standard
EF10.2*		1	PDF		2			
EF10.3*		1	PDF		3			
EF03.1		1	PDF	1 N.O.	1			
EF03.2		1	PDF		2			
EF03.3		1	PDF		3			
EF110.1*		1	PDF	2 N.C.	1			
EF110.2*		1	PDF		2			
EF110.3*		1	PDF		3			
EF033.1		1	PDF	2 N.O.	1			
EF033.2		1	PDF		2			
EF033.3		1	PDF		3			
EF103.1*		1	PDF	1 N.C. / 1 N.O.	1			
EF103.2*		1	PDF		2			
EF103.3*		1	PDF		3			
EF220.1**		1	PDF	2 N.C.	1			Emergency Stop
EF220.2**		1	PDF		2			
EF220.3**		1	PDF		3			
EF303.1**		1	PDF	1 N.C. / 1 N.O.	1			
EF303.2**		1	PDF		2			
EF303.3**		1	PDF		3			

*Not suitable for Emergency Stop devices

**Not suitable for maintained selector switches NWS/NWT

Travel Diagram Legend

= contact closed
 = contact open



Numbers indicate distance in mm

Mounting Flange			
Part Number	Price	Description	Drawing Link
EFM		Schmersal mounting flange, replacement. For use with E and N series pushbuttons.	PDF

Contact Blocks and Light Terminal Blocks Overview

Features

- A self-cleaning contact bridge system, known as Elan four-way system, which is particularly suitable for low voltage applications and has a lower switching capacity of 5VDC/3.2 mA (max. 400VAC/8A). It is designed in the form of a bent twin contact bridge, with parallel and also diagonal operation.
- Block mounting via snap-on stainless steel springs.
- Complete terminal designations visible at a glance in compliance with IEC 60 947-1 (VDE 0660, Part 100) with a complete function and sequence number (refer also to product ranges). The function number identifies the N.C. and N.O. contact. The sequence number specifies the number and the order of the contacts on the complete switching device.
- N.C. contacts with positive opening in compliance with IEC 60 947-5-1 (VDE 0660 Part 200).
- Galvanically isolated contact circuits in 2-pole blocks.
- High resistance to shock and vibrations.



Technical Specifications			
	Contact Blocks	Light Blocks (ELE)	Light Blocks (ELDE)
General description	Contact element	Light terminal block w/Ba9S base	Light terminal block w/LED
Enclosure material	Plastic, glass fiber reinforced	Plastic, glass fiber reinforced	Plastic, glass fiber reinforced
Contact material	Fine-silver, phosphor bronze or brass carrier	-	-
Utilization category	AC-15: 250 V / 8 A DC-13: 24 V / 5 A	-	-
Suitability for low voltages	≥ 5VDC / 3.2 mA	-	-
Rated insulation voltage U_i	400V	440V	440V
Rated impulse withstand voltage U_{imp}	4kV	-	-
Thermal test current I_{the}	10A	-	-
Max. fuse rating	10A gG D-fuse slow blow	10A gG T-slow blow	10A gG T-slow blow
Wire size	0.5 mm ² to 2.5 mm ² (20 - 14 AWG)		
Tightening torque wire connection	Maximum 1 N·m (0.74 lb·ft)		
NEMA contact rating	A300 / P300	-	-
Switching frequency	1200 s/h	-	-
Switching capacity	5VDC / 3.2 mA (max 400VAC / 8A)	-	-
Mechanical life	10,000,000 operation	-	-
Resistance to shock	110 g/4ms to 30 g/18ms no bouncing	-	-
Resistance to vibration	> 20 g/10ms to 200Hz	-	-
Ambient temperature	-25 to +80°C [-13 to +176°F]		
Ingress protection rating	IP20 terminals / IP40 switching compartment	IP20 terminals	IP20 terminals
Standards	IEC 60947-5-1; IEC 60947-1; UL File E57648		


NEMA Contact Rating Designation			
	Thermal Current	Voltage	Voltamperes
A300	10	300 AC	N/A
P300	5	300 DC	138



NB



NDP-70-ES





EDT-25-5ST



NZSO-V4A

IP69K Accessories			
Part Number	Price	Drawing Link	Description
<u>NB</u>		PDF	Hole seal/blanking plug, silver, 44.5 mm diameter, ABS/chrome-plated, 1/ea
<u>NDP-70-ES</u>		PDF	Legend plate, metallic, round, yellow field, yellow background, black engraved text, legend plate text "Emergency Stop". For use with 22mm pushbuttons. 1/ea
<u>NUE</u>		PDF	Pilot device hole adapter, reduces from 30.5 mm to 22.3 mm. Adapter ring, seal and washer included. 1/ea
<u>EDT-25-5ST</u>		PDF	Spare seals, 5/bag
<u>NZSO-V4A</u>		PDF	Legend plate - blank, stainless steel, 1/ea




SCHMERSAL Control and Signaling Devices 22mm IP69K

Schmersal control and signaling devices have a number of special design features that make the devices suitable for food processing, pharmaceutical, and medical applications. When utilized in food processing machines, these devices comply with the special cleaning requirements of the industry to prevent cross-contamination, particularly when used in machines that process raw goods. With an ingress protection rating of IP69K, Schmersal control and signaling devices are also suitable for marine applications, traffic systems, commercial vehicles, and in dusty and dirty environments.

Features

- Special seals prevent product residue from penetrating in the gaps between the fixed and moving device parts, thus preventing the collection of dirt and bacteria in places that are not easily accessible for cleaning.
- Smooth designs make the devices easy to clean.
- Modular contact and light terminal blocks make the devices easy to install.




IP69K Ingress Protection Rating Overview

IP69K high-pressure cleaning test

This rating applies to devices tested in accordance with DIN 40050-9. The goal of this test is to duplicate pressure cleaning conditions on a plant floor. In the test fixture, the devices are exposed to a 1450psi spray of water at a temperature of 175°F. The duration of each cleaning cycle is 30 seconds. The test is performed at specified angles using a spray nozzle located at a distance of 4" from the devices. Devices with this rating must withstand test conditions and still be operable. This rating ensures water proofing protection that exceeds NEMA 4X rating.

Thermal endurance

In pressure environments, controls and signaling devices can be exposed to extreme temperature conditions. To meet the criteria for IP69K rating, devices must undergo a thermal shock test by cycling the environmental temperature to ensure consistent high reliability.




Pilot Devices

tPIL-60

SCHMERSAL Modular Design Flexibility

Non-Illuminated Devices



Illuminated Devices

