

FlatSIGN Signal Lights

WERMA FlatSIGN Features

- Industrial signal light
- Red/Yellow/Green LEDs
- Permanent or blinking (DIP switch selectable)
- 160-degree viewing angle
- Wall mount installation
- Audible alert option with 8 DIP switch-selectable tones (DC models) or continuous (AC models)
- 2 year warranty



691 Series FlatSIGN Technical Specifications																							
Part Number	Price	Drawing Link	Description	Voltage	Housing Color	Current	Operating Temp /Protection	Life Duration	Housing Material	Weight g [oz]	Wiring Diagram	Connection	Agency Approval										
Base Mount																							
69110055		PDF	Permanent or blinking LED	24V AC/DC	Transparent	30mA per tier	-30 to +50°C (-22 to +122°F) IP65 when mounted	max. 50,000h	PC transparent or coated cap/PC/ABS blend housing	230 [8.11]	Diagram 1	Membrane grommet	UL file E164155, CE, RoHS										
69130055		PDF			Silver																		
69110068		PDF		115-230 VAC	Transparent																		
69130068		PDF			Silver																		
69120055		PDF	Permanent or blinking LED Audible alert (8 selectable tones, 80dB at 1 meter)	24V AC/DC	Transparent					30mA per tier	-30 to +50°C (-22 to +122°F) IP65 when mounted	max. 50,000h		PC transparent or coated cap/PC/ABS blend housing	235 [8.29]	Diagram 2	Terminal screw 0.5 -1.5 mm ²	UL file E164155, CE, RoHS					
69140055		PDF			Silver																		
69120068		PDF	Permanent or blinking LED Audible alert (continuous tone, 80dB at 1 meter)	115-230 VAC	Transparent										30mA per tier	-30 to +50°C (-22 to +122°F) IP65 when mounted	max. 50,000h		PC transparent or coated cap/PC/ABS blend housing	235 [8.29]	Diagram 2	Terminal screw 0.5 -1.5 mm ²	UL file E164155, CE, RoHS
69140068		PDF			Silver																		

Wiring Diagrams

